

### Trumbull Manufacturing

3850 Hendricks Road, Youngstown, Ohio 44515

Phone: 330.270.7888 | 877.504.1507 | 330.392.0756

Toll Free:

Fax:

-www.trumbull-mfg.com

# Double Socket Ratchet Wrenches

- ADIUSTABLE HANDLE HELPS GET TO
- Heavy-duty double socket incorporates a through design which can tighten nuts on long bolts or all-thread rod without bottoming out.
- Double socket permits use on either 5/8" or 3/4" Heavy Hex Nuts without changing sockets. Also eliminates common misplacement of loose sockets and introduction of dirt into the mechanism while changing sockets in the field.
- Mechanism design allows short stroke operation.

 Heavy-duty ratchet mechanism is lubricated and enclosed in a sealed ductile iron casting to prevent debris from jamming.

- Wrench is 16" OAL.
- Painted black.



THOSE HARD-TO-REACH NUTS AND BOLTS!

ADJUSTABLE HANDLE ILLUSTRATION.

### PLATED STEEL BOLT AND WING NUT

lock heavy duty 12" ductile iron handle to the ratchet head

### **EASY ACTION LEVER**

reverses direction



**SLIP RESISTANT RESILIENT GRIP** 

#### WING NUT AND BOLT

can be installed from either side of assembly to minimize interference

#### **OILER FEATURE**

allows for easy lubrication without disassembly

## **DOUBLE SOCKET DESIGN** Small socket fits heavy hex nuts on 5/8"

bolts used on clamps, couplings, saddles and 3" Mechanical Joints. Large Socket fits heavy hex nuts on 3/4" bolts, used on 4" through 24" Mechanical Joints.

| Item №   | Large<br>Socket | Small<br>Socket | Large Socket<br>Fits Hex Size | Small Socket<br>Fits Hex Size | EXAMPLES OF LARGE SOCKET APPLICATIONS                     | EXAMPLES OF SMALL SOCKET APPLICATIONS | Weight    |
|----------|-----------------|-----------------|-------------------------------|-------------------------------|---|---------------------------------------|-----------|
| 364-9984 | 1-1/4″          | 1-1/16"         | 3/4" Heavy                    | 5/8" Heavy                    | 4" thru 24" MJ Ftgs.,<br>3/4" Hex Bolts<br>with Heavy Hex | 3″ MJ Ftgs.,<br>Cast Couplings        | 4.75 lbs. |
| 364-9955 | 36mm            | 30mm            | M24                           | M20                           | 400mm - 500mm<br>Pipe Flanges                             | 200mm - 350mm<br>Pipe Flanges         | 2.15 KG   |